

Potassium Silicate Solution 42,5° BE
00359-1160

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Potassium Silicate Solution 42,5° BE

Art.-No.

592 0220, 592 0230

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

bonding material

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflächenschutz Elbe GmbH

Heuweg 4

D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number: Emergency telephone :+49 (0) 6132 / 84463 (GBK GmbH, Ingelheim)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant

R phrases:

Irritating to eyes and skin.

GHS classification

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

2.2. Label elements

Pictograms: GHS07



Signal word: Warning

Hazardous components which must be listed on the label

Potassium silicate

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P262 Do not get in eyes, on skin, or on clothing.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

High risk of slipping due to leakage/spillage of product.

Potassium Silicate Solution 42,5° BE
00359-1160

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
215-199-1	Potassium silicate (Mole ratio K ₂ O : SiO ₂ = 1 : > 2,60 - < 3,20)	30 - 50 %
1312-76-1	Xi - Irritant R36/38	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	
01-2119456888-17		

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Not known.

5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.

Potassium Silicate Solution 42,5° BE
00359-1160

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.
Avoid contact with skin, eyes and clothing.
High risk of slipping due to leakage/spillage of product.

6.2. Environmental precautions

Clean contaminated surface thoroughly.
Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Keep from freezing.

Advice on storage compatibility

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.
When using, do not eat, drink or smoke.
Remove and wash contaminated clothes before re-use.
Avoid contact with eyes, skin or mucous membrane.

Respiratory protection

No personal respiratory protective equipment normally required.
Breathing apparatus in the event of aerosol or mist formation. Short term: filter apparatus, Filter B

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Potassium Silicate Solution 42,5° BE
00359-1160

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Eye protection

Tightly fitting goggles.
Eye wash bottle with pure water.

Skin protection

Long sleeved clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Colourless, clear
Odour: Odourless

	Test method
pH-Value (at 20 °C):	Alkaline
Changes in the physical state	
Boiling point:	100 °C
Flash point:	n.a.
Lower explosion limits:	n.d.
Ignition temperature:	n.d.
Density (at 20 °C):	1,42 g/cm ³
Water solubility: (at 20 °C)	Completely miscible
Viscosity / dynamic: (at 20 °C)	50 mPa·s

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Exothermic reaction with strong acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

LD50/oral/rat: > 2000 mg/kg (The toxicological data has been taken from products of similar composition.)

Irritation and corrosivity

Skin irritation: Irritant

Eye irritation: Irritant

Sensitising effects

Not classified.

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Not classified.

STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

Potassium Silicate Solution 42,5° BE
00359-1160

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified.
Mutagenicity: Not classified.
Teratogenicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

Methods for the determination of biodegradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

The product is an alkaline solution. Neutralization is normally necessary before a waste water is discharged into sewage treatment plants.

When low concentrations are discharged correctly into adapted biological sewage treatment plants, interference with the degradation activity of activated sludge is not likely.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Other applicable information

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.



Potassium Silicate Solution 42,5° BE
00359-1160

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

36/38 Irritating to eyes and skin.

Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)